
Stellin Ivo

stageplan











| Channel | Instrument | Mic |
|---------|-------------------|-----------------------------|
| 01 | Kick | Provided by engineering FOH |
| 02 | Snare | Provided by engineering FOH |
| 03 | Hi Hat | Provided by engineering FOH |
| 04 | Tom 1 | Provided by engineering FOH |
| 05 | Tom 2 | Provided by engineering FOH |
| 06 | Tom Floor 1 | Provided by engineering FOH |
| 07 | Tom Floor 2 | Provided by engineering FOH |
| 08 | Overhead left | Provided by engineering FOH |
| 09 | Overhead right | Provided by engineering FOH |
| 10 | Bass | DI |
| 11 | Guitar 1 | E906* |
| 12 | Guitar 2 | E906* |
| 13 | Keys (DI) | DI |
| 14 | Keys (DI) | DI |
| 15 | (Acoustic Guitar) | DI |
| 16 | Voc 1 | Beta 58* |
| 17 | Voc 2 | Beta 58* |
| 18 | Voc 3 | SM 58* |
| 19 | | |

*own mics

System requirements

Monitoring: 5x InEar monitoring, 1 channel per mix for each musician

Drumpodium: provide a drum podium, approximately 2,5 m x 2 m x 0,4 m (W x D x H)

Attention: Please don't set up any wedge monitors

Mixing desk: Digital console, minimal 24 channels, 8 x aux, · minimal 4 subgroups with

inserts, minimal 3 Band parametr. EQ

Ambiente: Depending about the size of the room, please provide one or two room

microphones

Dynamics: Selection by engineering FOH

Playback / Intro: CD-Player for Intro / or connection for USB stick (mp3)

Front: PA System, fitted according the size of the venue

Backdrop: Suspension device for banner 3 x 2 m (or 5 x 3 m)

Light effects: No stage fog

Voltage: 230 V /16 A Power supply with separated power lines for audio / light

protected by RDC

If parts of this list cannot be fulfilled, please feel free to get contact with Fredy Koller, +41 78 617 70 67 or Email: freedy@stationquo.ch